

ANTONIO



Guarantee

Garantie

Garantie

Garantie



Product information
Produkt informatie

Produkt Daten
Information produit





	Total thickness Totale dikte	Gesamtstärke Epaisseur totale	EN 428	2,75 mm
	Wearlayer Slijtlaag	Nutzschicht Couche d'usure	EN 429	0,25 mm
	Width Breedte	Breite Largeur	EN 426	4m 5m
	Standard length Standard rollengte	Standard Rollenlänge Longueur standard	EN 426	25m 22m
	Total roll weight Totaal rolgewicht	Total Rollengewicht Poids total des rouleaux		210kg - 235kg
	Classification Classificatie	Klassifizierung Classification	EN 653	23
				31

Technical information
Technische informatie

Technische Daten
Information technique

	Light stability Lichtechtheid	Lichtechtheit Résistance à la lumière	ISO 105-B02	≥ 6
	Dimensional stability Dimensionele stabiliteit	Dimensionsstabilität Stabilité dimensionnelle	EN 434	≤ 0,40%
	Underfloor heating Vloerverwarming	Fussbodenheizung Chauffage par le sol	EN 12667	Suitable Geschikt Geeignet Convenable

ANTONIO

	Residual indentation Restindrukking	Eindruckverhalten Poinçonnement	EN 433	≤ 0,35 mm
	Impact sound improvement Contactgeluidsisolatie	Trittschallschutz Isolation acoustique	EN ISO 717/2	ΔLw 14dB
	Reaction to fire Brandklasse	Brandverhalten Indice d'incendie	EN 13501-1	B _{fl} S1
	Slipresistance Slipweerstand	Rutschhemmung Glissance	DIN 51130	<div style="border: 1px solid black; padding: 2px; text-align: center;"> Ultragrip R10 Classification </div>
	Castor chair Rolstoel	Rolstuhl Chaise à roulette	EN 425	Suitable Geschikt Geeignet Convenable



B.I.G. Floorcoverings
Rijksweg 442
8710 - Wielsbeke

06

EN 14041:2004

Expanded (cushioned) polyvinyl
chloride floor coverings (EN653)

Reaction to fire : Class Bfl/s1

Slipperiness : DS

Formaldehyde : E1

EN 653