

SANDRO



Guarantee

Garantie





Garantie

Garantie



	Product information Produkt informatie	Produkt Daten Information produit		
	Total thickness Totale dikte	Gesamtstärke Epaisseur totale	EN 428	3,25 mm
	Wearlayer Slijtlaag	Nutzschicht Couche d'usure	EN 429	0,35 mm
	Width Breedte	Breite Largeur	EN 426	4m 5m
	Standard length Standard rollengte	Standard Rollenlänge Longueur standard	EN 426	22m 20m
	Total roll weight Totaal rolgewicht	Total Rollengewicht Poids total des rouleaux		210kg - 240kg
	Classification Classificatie	Klassifizierung Classification	EN 653	23
				31

	Technical information Technische informatie	Technische Daten Information technique		
	Light stability Lichtechtheid	Lichtechtheit Résistance à la lumière	ISO 105-B02	≥ 6
	Dimensional stability Dimensionele stabiliteit	Dimensionsstabilität Stabilité dimensionnelle	EN 434	≤ 0,40%
	Underfloor heating Vloerverwarming	Fussbodenheizung Chauffage par le sol	EN 12667	Suitable Geschikt Geeignet Convenable

SANDRO				
	Residual indentation Restindrukking	Eindruckverhalten Poinçonnement	EN 433	≤ 0,35 mm
	Impact sound improvement Contactgeluidsisolatie	Trittschallschutz Isolation acoustique	EN ISO 717/2	ΔLw 18dB
	Reaction to fire Brandklasse	Brandverhalten Indice d'incendie	EN 13501-1	B _f S1
	Slipresistance Slipweerstand	Rutschhemmung Glissance	DIN 51130	<div style="border: 1px solid black; padding: 2px; display: inline-block;"> Ultragrip R10 Classification </div>
	Castor chair Rolstoel	Rolstuhl Chaise à roulette	EN 425	Suitable Geschikt Geeignet Convenable

CE
B.I.G. Floorcoverings Rijksweg 442 8710 - Wielsbeke
06
EN 14041:2004
Expanded (cushioned) polyvinyl chloride floor coverings (EN653)
Reaction to fire : Class Bf/s1
Slipperiness : DS
Formaldehyde : E1
EN 653